

|                                        |                        |                                                               |
|----------------------------------------|------------------------|---------------------------------------------------------------|
| WAAS<br>CH <b>45602</b><br><b>W21B</b> | APP CRS<br><b>210°</b> | Rwy Idg <b>6801</b><br>TDZE <b>626</b><br>Apt Elev <b>640</b> |
|----------------------------------------|------------------------|---------------------------------------------------------------|

RNAV (GPS) Z RWY 21  
CHARLOTTESVILLE-ALBEMARLE (CHO)

RNP APCH.

- T** Baro-VNAV NA when using Staunton/Waynesboro/Harrisonburg altimeter setting.  
For uncompensated Baro-VNAV systems, procedure NA below -16°C or above 54°C.  
**A** When local altimeter setting not received, use Staunton/Waynesboro/Harrisonburg altimeter setting and increase all DA 130 feet and LPV visibility 1/8 mile.

**MISSED APPROACH:** Climb to 1100, then climbing left turn to 4000 direct GVE VORTAC and hold.

|                 |                                   |                                                   |                          |                  |
|-----------------|-----------------------------------|---------------------------------------------------|--------------------------|------------------|
| ATIS<br>118.425 | POTOMAC APP CON<br>132.85 323.125 | CHARLOTTESVILLE TOWER ★<br>124.5 (CTAF) 0 338.275 | GND CON<br>121.9 338.275 | UNICOM<br>122.95 |
|-----------------|-----------------------------------|---------------------------------------------------|--------------------------|------------------|

