

WAAS CH 86410 W30A	APP CRS 300°	Rwy Idg TDZE 549 Apt Elev 549
--	------------------------	---

RNAV (GPS) RWY 30

JEFFERSON CITY MEML (JEF)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). DME/DME RNP-0.3 NA.


⚠ When local altimeter setting not received, use Columbia Rgnl altimeter setting and increase all DA/MDA 80 feet; increase LPV all Cats, LNAV/VNAV all Cats, LNAV Cats B, C, and D, and Circling Cats A, B and C visibility ¼ SM. For inoperative MALSR, when using Columbia Rgnl altimeter setting increase LPV all Cats visibility to 1¼. Baro-VNAV and VDP NA when using Columbia Rgnl altimeter setting. Circling Rwy 9 NA at night.

MALSR



MISSED APPROACH: Climb to 3000 direct GIBSN and hold.

ASOS 133.625	MIZZU APP CON 124.375 353.925	JEFFERSON CITY TOWER ★ 125.6 (CTAF) 	GND CON 121.7	UNICOM 122.95
------------------------	---	---	-------------------------	-------------------------



ELEV 549 TDZE 549



REIL Rwy 9, 12, and 27 

MIRL Rwy 9-27

HIRL Rwy 12-30 

3000	GIBSN	VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 50).				4 NM Holding Pattern
* LNAV only.		* 2 NM to RW30		ERINE		FATPI
						2800
2 NM		2.3 NM		6.1 NM		GP 3.00° TCH 54
CATEGORY	A	B	C	D		
LPV DA	799-½		250 (300-½)			
LNAV/VNAV DA	1322-2¼		773 (800-2¼)			
LNAV MDA	1240-½ 691 (700-½)		1240-1½ 691 (700-1½)		1240-1¾ 691 (700-1¾)	
 CIRCLING	1320-1 771 (800-1)		1320-1¼ 771 (800-1¼)		1320-2¼ 771 (800-2¼)	
				1560-3 1011 (1100-3)		