

WAAS
CH **93702**
W06A

APP CRS
057°

Rwy Idg
TDZE **2351**
Apt Elev **2351**

RNAV (GPS) RWY 6

GENERAL WM J FOX AIRFIELD (WJT')

▼ When VGSI inop, Straight-in/Circling Rwy 6 procedure NA at night.

▲ DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 45°C (113°F). When local altimeter setting not received, use Palmdale altimeter setting: increase LPV DA to 2661 feet, LNAV/VNAV DA to 2709 feet and all MDAs 60 feet, and increase Circling Cats C/D visibility ¼ SM. Baro-VNAV NA when using Palmdale altimeter setting.

MISSED APPROACH: Climb to 6000 direct SISOY and via 091° track to ETHER and hold.

ATIS 126.3	JOSHUA APP CON 126.1 290.3	FOX TOWER* 118.525 (CTAF) 256.9	GND CON 121.7 256.9	UNICOM 122.95
----------------------	--------------------------------------	---	-------------------------------	-------------------------

ETHER

249°

069°

7 NM

SISOY

2389

Λ 2630

2767

Λ 2630

091°

HONUL

(FAF) GUVDE

5500

057°

(3.5)

4004±

3884

3795

Λ 4333

3807

Λ 4850

5200

5303

Λ 3600

Λ 4485

Λ 3516

4000

5000

3000

5788

(IF)

JILMU

6400

057°

(2.7)

7000

(IAF) CASTA

6300

057°

(2.2)

MSA RW06 25 NM

9500

ELEV 2351	TDZE 2351
-----------	-----------

JILMU

HONUL

GUVDE

6000

SISOY

tr 091°

ETHER

7000

057°

6400

5500

*4100

RW06

*LNAV only.

Procedure Turn NA

GP 3.00°

TCH 40

2.7 NM

3.5 NM

4.1 NM

5.4 NM

CATEGORY	A	B	C	D
LPV DA	2601-1 250 (300-1)			
LNAV/VNAV DA	2649-1 298 (300-1)			
LNAV MDA	2940-1 589 (600-1)		2940-1½ 589 (600-1½)	2940-1¾ 589 (600-1¾)
CIRCLING	2940-1 589 (600-1)		3120-2½ 769 (800-2½)	3120-2½ 769 (800-2½)

REIL Rwys 6 and 24

MIRL Rwy 6-24

LANCASTER, CALIFORNIA

Orig-A 09SEP21

34°44'N-118°13'W

GENERAL WM J FOX AIRFIELD (WJT')

RNAV (GPS) RWY 6