

LOC/DME I-ONA 109.35 Chan 30 (Y)	APP CRS 300°	Rwy Idg TDZE 656 Apt Elev 656
--	------------------------	---

ILS Y or LOC Y RWY 30

WINONA MUNI-MAX CONRAD FIELD (ONA)

DME required.

VDP N/A with La Crosse altimeter setting. When local altimeter setting not received, use La Crosse altimeter setting and increase S-ILS 30 DA to 1127 and all visibilities ½ mile, increase all MDA 60 feet, and visibility S-LOC 30 Cat C/D ½ mile, and Circling Cat B ¼ mile. For inop ALS, increase S-ILS 30 all Cats visibility to 1¾ mile, increase S-LOC 30 Cats C/D visibility to 1¾ mile. For inop ALS when using La Crosse altimeter setting, increase S-ILS 30 all Cats visibility to 1¾ mile, increase S-LOC 30 Cats C/D visibility to 1¾ mile.

MALSR

MISSED APPROACH:
Climb to 1800 then climbing left turn to 3000 on RST VOR/ DME R-056 to VUZID INT and hold.

AWOS-3 118.075	MINNEAPOLIS CENTER 128.6 363.0	UNICOM 122.8 (CTAF)
--------------------------	--	-------------------------------

ELEV 656 D TDZE 656

REIL Rwy 12
MIRL Rwy 12-30

1800	3000	VUZID	Δ 2045
RST R-056			
*LOC only	*I-ONA		
I-ONA 0.9	I-ONA 2.5		
1.6 NM	3.7 NM	6 NM	
CATEGORY	A	B	C
S-ILS 30	1074-1 ½	418 (500-1 ½)	
S-LOC 30	1220- ½	564 (600- ½)	1220-1 ¼ 564 (600-1 ¼)
CIRCLING	1560-1 ¼ 904 (1000-1 ¼)	1600-1 ¼ 944 (1000-1 ¼)	1780-3 1124 (1200-3) 1980-3 1324 (1400-3)

WINONA, MINNESOTA

44°05'N-91°43'W

WINONA MUNI-MAX CONRAD FIELD (ONA)

Orig-B 11AUG22

ILS Y or LOC Y RWY 30