

WAAS CH 58141 W23A	APP CRS 230°	Rwy Idg 5501 TDZE 182 Apt Elev 182
--	------------------------	---

RNAV (GPS) RWY 23

SUMTER (SMS)

RNP APCH.

Circling NA to Rwy 14 and 32. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C or above 54°C. Inop table does not apply to LPV all Cats. For inop ALS increase LNAV/VNAV Cat A/B visibility to ¾ SM.

ODALS

MISSED APPROACH:
Climb to 600 then climbing left turn to 2400 direct GAUGH and hold.

AWOS-3
118.075

SHAW APP CON★
125.4

UNICOM
122.7 (CTAF) **0**

ELEV 182

TDZE 182

600

2400

GAUGH

*LNAV only.

WUMIS 2.6 NM to RW23

AGOZE 1900

GAUGH 4 NM Holding Pattern

050° → 6000

← 230° 2400

GP 3.00° TCH 44

1 NM

1.6 NM

2.7 NM

6 NM

CATEGORY	A	B	C	D
LPV DA	382-¾ 200 (200-¾)			
LNAV/VNAV DA	460-¾ 278 (300-¾)			
LNAV MDA	540-¾ 358 (400-¾)		540-⅞ 358 (400-⅞)	
CIRCLING	600-1 418 (500-1)	680-1 498 (500-1)	1000-2½ 818 (900-2½)	1000-2¾ 818 (900-2¾)

MIRL Rwy 5-23 **0**

REIL Rwy 5 and 23 **0**