CAMP RIPLEY, MINNESOTA

NDB RWY 31

NDB XCR 404	APCH CRS 301°	Rwy Idg 6100 THRE 1146 Arpt Elev 1150	AL-5226 [USA]	RAY S. MILLER AAF (KRYM)

T *Inop table does not apply to CAT AB. When ALS inop, increase CAT CD vis to 2 miles.
**Inop table does not apply to CAT A. When ALS inop, increase CAT B vis to 1¼ miles, CAT CD vis to 2 miles.
A NA

MALSF

MISSED APPROACH: Climbing right turn to 3000 in XCR NDB holding pattern.

MINNEAPOLIS CENTER	TOWER ★	CLNC DEL
118.05 239.0	126.2 L 254.4	126.2

Rwy 31 helicopter visibility reduction below ¾ mile NA.

Procedure NA when R-4301 is active.

R-4301
1542

When local altimeter setting not received, use Little Falls altimeter setting.

1650

Procedure not authorized via V510 and V2 northwest bound without holding at AXN. ATC clearance required.

1359
1339

HOLD 6000 3500
R-044
044°
200K
224°
3500
072°
(37.9)
121°
230K
301°
076°
256°
121°
1409
3500
337°
(34)
1692

IAF
RIPLEY
404 XCR

ALEXANDRIA
115.95 AXN
Chan 106Y

SAINT CLOUD
112.1 STC
Chan 58

MSA XCR 25 NM
3300

3000
XCR
NDB
2900
121°
2900
301°
Remain within 10 NM

ELEV 1150
THRE 1146

TWR
132°
6100 x 100
3500 x 80
13
31
Assault Strip
312°
1299
301°

HIRL Rwy 13-31 L

CATEGORY	A	B	C	D
S-31*	1860-1 714 (800-1)		1860-1¾ 714 (800-1¾)	
C CIRCLING	1860-1 710 (800-1)		1860-2 710 (800-2)	2080-3 930 (1000-3)
LITTLE FALLS ALTIMETER SETTING MINIMUMS				
S-31**	1900-1 754 (800-1)		1900-1⅞ 754 (800-1⅞)	
C CIRCLING	1900-1 750 (800-1)	1900-1¼ 750 (800-1¼)	1900-2¼ 750 (800-2¼)	2120-3 970 (1000-3)

CAMP RIPLEY, MINNESOTA — 46°05'N-94°21'W — RAY S. MILLER AAF (KRYM)

Amdt 4 05OCT23

NDB RWY 31

NC-1, 16 MAY 2024 to 13 JUN 2024