

WAAS
CH **40234**
W17A

APP CRS
175°

Rwy Idg
TDZE
Apt Elev

3704
27
28

RNAV (GPS) RWY 17
ORMOND BEACH MUNI (OMN)


⚠

Baro-VNAV NA when using Daytona Beach altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Daytona Beach altimeter setting and increase all DA 19 feet and all MDA 20 feet; increase LNAV Cat C visibility ½ mile. VDP NA when using Daytona Beach altimeter setting.

MISSED APPROACH:

Climb to 600 then climbing right turn to 2800 direct FLYHI and hold.

ATIS 118.475	DAYTONA APP CON 125.8 269.075	ORMOND BEACH TOWER* 119.075 (CTAF)	GND CON 121.625	CLNC DEL 121.625	UNICOM 123.05
------------------------	---	--	---------------------------	----------------------------	-------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.50/TCH 51).		600	2800	FLYHI
4 NM Holding Pattern		FLYHI		
2800 ← 355° → 175°		HATOS	GIGBE	*LNAV only.
GP 3.50° TCH 60		1600	2.2 NM to RWY 17	
		1600	*1.1 NM to RWY 17	
		900	RWY 17	
		7.4 NM	1.9 NM	1.1 NM
CATEGORY	A	B	C	D
LPV DA	302-1	275 (300-1)		NA
LNAV/VNAV DA	288-1	261 (300-1)		NA
LNAV MDA	400-1	373 (400-1)		NA
CIRCLING	500-1	471 (500-1)	740-2 711 (800-2)	NA

REIL Rwy 9, 17, 27, and 35

MIRL Rwy 9-27 and 17-35