

LOC/DME I-OGO
108.55
Chan **22 (Y)**

APP CRS
132°

Rwy Idg
TDZE **962**
Apt Elev **962**

ILS or LOC RWY 13

LIVINGSTON COUNTY SPENCER J HARDY (OZW)

▼


▲ NA

For inop ALS, increase LOC Cat C and D visibility to 1½ SM, and JIVEX fix minimums S-13 Cat C and D visibility to 1 SM.

MALSR

MISSED APPROACH: Climb to 1600 then climbing right turn to 3000 heading 356° and I-OGO NW course to HUCCY INT/ I-OGO 11.3 DME and hold.

AWOS-3 118.875	DETROIT APP CON 132.35 284.0	CLNC DEL 121.725 (GCO)	UNICOM 123.0 (CTAF) 0
--------------------------	--	----------------------------------	---------------------------------



One Minute Holding Pattern

HUCCY INT I-OGO 11.3

5000 ← 312°

3000 → 132°

GS 3.00° TCH 48

2500

DURG INT I-OGO 5.7

JIVEX INT I-OGO 3.1

1600

3000

hdg 356° I-OGO NW crs

HUCCY INT

ELEV 962

TDZE 962

132°

CATEGORY	A	B	C	D
S-ILS 13	1162-½ 200 (200-½)			
S-LOC 13	1540-½	578 (600-½)	1540-1¼	578 (600-1¼)
CIRCLING	1540-1	578 (600-1)	1600-1¾ 638 (700-1¾)	1600-2 638 (700-2)
JIVEX FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)				
S-LOC 13	1320-½	358 (400-½)	1320-⅝	358 (400-⅝)
CIRCLING	1400-1 438 (500-1)	1420-1 458 (500-1)	1600-1¾ 638 (700-1¾)	1600-2 638 (700-2)

HIRL Rwy 13-31 0

REIL Rwy 31 0

FAF to MAP 4.7 NM

Knots	60	90	120	150	180
Min:Sec	4:42	3:08	2:21	1:53	1:34