

APP CRS
348°


Rwy Idg
TDZE
Apt Elev
8598
24
27

RNAV (RNP) Z RWY 35L
SACRAMENTO INTL (SMF)

RNP AR APCH-GPS.
For uncompensated Baro-VNAV systems, procedure NA below -2°C or above 54°C. For inop ALS, increase RNP 0.12 all Cats visibility to RVR 4500; increase RNP 0.30 all Cats visibility to RVR 5500.

MALSR
MISSED APPROACH: Climb to 2000 on track 348° to JARNU and track 321° to GRIME and hold.

D-ATIS 126.75	NORCAL APP CON 125.4 259.1 (W-NE) 125.25 257.9 (SW) 127.4 317.5 (E-SE)	CAPITOL TOWER 125.7 256.7	GND CON 121.7 256.7	CLNC DEL 121.1 256.7	CPDLC
-------------------------	---	-------------------------------------	-------------------------------	--------------------------------	-------



ELEV 27 TDZE 24

TDZ/CL Rwy 17L and 17R
HIRL Rwy 17R-35L and 17L-35R

GP 3.00°
TCH 59

3.2 NM

348°

1100

321°

2000

JARNU

GRIME

tr 348°

tr 321°

See planview for multiple IF locations.

CATEGORY	A	B	C	D
RNP 0.12 DA	318/24 294 (300-1/2)			
RNP 0.30 DA	382/30 358 (400-5/8)			

AUTHORIZATION REQUIRED