

VOR/DME MML <u>111.0</u> Chan 47	APP CRS 130°	Rwy Idg 7221 TDZE 1183 Apt Elev 1183
---	------------------------	---

VOR RWY 12
HALL/RYAN FLD (MML)

SOUTHWEST MINNESOTA RGNL MARSHALL/RYAN FLD (MML)

	For inop ALS, increase S-12 Cat C/D visibilities to 1% SM, CEGUL fix minimums: S-12 Cat C/D visibility to 1 SM. For inop ALS when using Tracy altimeter setting increase S-12 Cat C/D visibilities to 1% SM. When local altimeter setting not received, use Tracy Muni altimeter setting and increase all MDAs 60 feet, S-12 Cat C/D visibility $\frac{1}{2}$; Circling Cat C/D visibility $\frac{1}{4}$ SM; CEGUL fix minimums: increase Circling C/D visibility $\frac{1}{4}$ SM. VDP NA when using Tracy Muni altimeter setting.		MISSED APPROACH: Climb to 2000, then climbing left turn to 2800 direct MML VOR/DME and hold.
---	---	---	---

AWOS-3PT 120.150	MINNEAPOLIS CENTER 127.1 290.2	GCO 121.725	UNICOM 122.8 (CTAF) ①
----------------------------	--	-----------------------	---------------------------------

