

LOC/DME I-LVK

110.5

Chan 42

APP CRS

255°

Rwy ldg

5253

TDZE

400

Apt Elev

400

LOC RWY 25R

LIVERMORE MUNI (LVK)

⚠

Circling to Rwy 25L NA at night.
Inop table does not apply to S-25R Cats C/D.
Circling NA north of Rwy 7L-25R.
DME required.

MALS R

A5

MISSED APPROACH: Climb to 2000 then climbing right turn to 5000 on heading 020° and OAK VOR/DME R-060 to ALTAM/OAK VOR/DME 23.3 DME and hold, continue climb-in-hold to 5000.
*Missed approach requires minimum climb of 235 feet per NM to 3600.

ATIS 119.65	NORCAL APP CON 123.85 278.3	LIVERMORE TOWER ★ 118.1(CTAF) 239.25	GND CON 121.6	UNICOM 122.95
----------------	--------------------------------	---	------------------	------------------

Enroute chart for Livermore Muni (LVK) showing various navigation aids, altitudes, and distances. Key features include:

- LOC/DME 110.5 (Chan 42):** Localizer and Distance Measuring Equipment for Runway 25R.
- Altitudes:** Minimum altitudes (MAs) for various segments: 3902, 2600, 1190, 1762, 1262, 1224, 585±, 480±, 1289, 694, 841±, 1980, 1264, 3100, 255° (6.2), 3100, 261° (26.4), 3100, 209° (33.1).
- Distances:** 116.8 OAK (Chan 115), 23.3 OAK, 5.9 ZABGO I-LVK, 9.3 JUSOM I-LVK, 7.4 HINIX I-LVK, 1.5 UHHUT I-LVK, 1.5 LIN (Chan 95).
- Obstacles:** 1805, 2328, 2986, 3033, 3065, 3380, 3675, 3024, 3817, 3065, 3380.
- Procedure:** Procedure NA for arrivals at LIN VOR/DME on V108 eastbound.

ELEV 400

TDZE 400

HIRL Rwy 7L-25R

MIRL Rwy 7R-25L

2000

5000

hdg 020°

OAK R-060

ALTAM

HINIX I-LVK 7.4

JUSOM I-LVK 9.3

UHHUT I-LVK 15.5

I-LVK 1

ZABGO I-LVK 5.9

3100

255°

3100

2520

2000

2.9 NM

1.5 NM

1.9 NM

6.2 NM

CATEGORY	A	B	C	D
S-LOC 25R*	1080-1½	680 (700-1½)	1080-1½	680 (700-1½)
S-LOC 25R	2000-¾ 1600 (1600-¾)	2000-1 1600 (1600-1)	2000-3	1600 (1600-3)
CIRCLING	2000-1¼ 1600 (1600-1¼)	2000-1½ 1600 (1600-1½)	2000-3	1600 (1600-3)

LIVERMORE, CALIFORNIA

Amtd 1 07DEC17

37°42'N-121°49'W

LIVERMORE MUNI (LVK)

LOC RWY 25R