

WAAS CH 58011 W18A	APP CRS 180°	Rwy Idg 3998 TDZE 83 Apt Elev 83
--	------------------------	---

RNAV (GPS) RWY 18

JOHN H HOOKS JR MEML (M79)

RNP APCH - GPS.

NA

Rwy 18 helicopter visibility reduction below 1 SM NA. Straight-in and Circling Rwy 18 NA at night. Use Monroe altimeter setting, when not received, use Bastrop altimeter setting and increase all DA/MDA 20 feet; increase LPV all Cats visibility 1/8 SM. Baro-VNAV NA.

MISSED APPROACH:
Climb to 1600 direct
APERE and hold.

MLU ASOS
125.05

MONROE APP CON ★
126.9

UNICOM
122.8 (CTAF) 0

1149

△

4 NM

6000

1700

80°

360°

(IF/IAF)

OGELS

1600

180°

(6.9)

(FAF)

YIGLU

ZAPOR

1.3 NM to RW18

△ 298

△ 187±

△ 492

△ 131±

△ 335

MISSED APCH FIX

APERE

360°

180°

4 NM

30 NM to OGELS (NoPT)

9 NM

2200

1700

090°

270°

OGELS

9 NM

2200

1700

30 NM to OGELS

ELEV 83

TDZE 83

180°

81

5.7 X 869

36

REIL Rwy 18 and 36 0

MIRL Rwy 18-36 0

1600

APERE

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 50).

4 NM Holding Pattern

360°

180°

6000

1700

GP 3.60°

TCH 59

*640 When using Bastrop altimeter setting.

YIGLU

1600

ZAPOR

1.3 NM to RW18

△ 298

△ 187±

△ 492

△ 131±

△ 335

MISSED APCH FIX

APERE

360°

180°

4 NM

1.3 NM

2.5 NM

6.9 NM

CATEGORY

A

B

C

D

LPV DA

448-1

365 (400-1)

NA

NA

RNAV/VNAV DA

559-1 3/8

476 (500-1 3/8)

NA

NA

RNAV MDA

480-1

397 (400-1)

NA

NA

CIRCLING

600-1

517 (600-1)

NA

NA

RAYVILLE, LOUISIANA
Amdt 1C 29DEC22

32°29'N-91°46'W

JOHN H HOOKS JR MEML (M79)

RNAV (GPS) RWY 18

SC-4, 18 APR 2024 to 16 MAY 2024

SC-4, 18 APR 2024 to 16 MAY 2024