



WAAS CH 72739 W21A	APP CRS 204°	Rwy Idg TDZE 157 Apt Elev 160
--	------------------------	---

RNAV (GPS) RWY 21

WILSON INDUSTRIAL AIR CENTER (W03)

RNP APCH.	▼ NA Circling Rwy 9, 15, 27, 33 NA at night. Obtain local altimeter setting on CTAF; when not received, use Rocky Mount altimeter setting and increase all MDA 20 feet; increase LP Cats C and D visibility 1⁄8 SM. Rwy 21 helicopter visibility reduction below 3⁄4 SM NA.	MISSED APPROACH: Climb to 1000, then climbing right turn to 2500 direct FEBEL and hold.
-----------	--	--

WASHINGTON CENTER 123.85 279.65	UNICOM 123.0 (CTAF) 0
---	---------------------------------



1000	2500	FEBEL	4 NM Holding Pattern	
↑	↗	△		
CEDNA		DIPTE	FEBEL	
ZAKAM 1.1 NM to CEDNA		1800	024° → 6000 ← 204° 2500	
700		3.04° TCH 40		
0.5 1.1 NM		3.4 NM	6.5 NM	
CATEGORY	A	B	C	D
LP MDA	520-1 363 (400-1)			
LNAV MDA	540-1 383 (400-1)		540-1½ 383 (400-1½)	
CIRCLING	660-1 500 (500-1)		780-1¾ 620 (700-1¾)	780-2 620 (700-2)