WAAS CH 57930 W22A	APP CRS 220°	Rwy ldg 3600 TDZE 1171 Apt Elev 1171

RNAV (GPS) RWY 22
IOWA COUNTY (MRJ)

Baro-VNAV NA when using Platteville altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). When local altimeter setting not received, use Platteville altimeter setting and increase all DA 55 feet, increase LPV all Cats visibility ⅛ mile and LNAV/VNAV all Cats visibility ¼ mile, increase all MDA 60 feet, and LNAV Cat C visibility ¼ mile. DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 3500 direct ZUPOV and hold.

AWOS-3	CHICAGO CENTER	UNICOM
118.525	133.95 281.4	122.8 (CTAF) L



ELEV 1171	TDZE 1171



CATEGORY	A	B	C	D
LPV DA	1371-¾ 200 (200-¾)			NA
LNAV/VNAV DA	1479-1 308 (400-1)			NA
LNAV MDA	1580-1 409 (500-1)		1580-1⅛ 409 (500-1⅛)	NA
CIRCLING	1620-1 449 (500-1)	1640-1 469 (500-1)	1640-1½ 469 (500-1½)	NA

REIL Rwys 11 and 29 L
MIRL Rwys 4-22 and 11-29 L

EC-3, 16 MAY 2024 to 13 JUN 2024
EC-3, 16 MAY 2024 to 13 JUN 2024