



APP CRS 332°	Rwy Idg	4504
	TDZE	269
	Apt Elev	269

RNAV (GPS) RWY 33

GIDEON MEML (M85)

NA	DME/DME RNP-0.3 NA. Procedure NA at night. Helicopter visibility reduction below 1 SM NA. Obtain Arkansas Intl altimeter setting on CTAF (122.7), when not received, use Poplar Bluff altimeter setting and increase all MDA 20 feet and Circling Cat C visibility ¼ mile.	MISSED APPROACH: Climb to 2400 direct UMEMY and hold.

BYH CTAF 122.7	MEMPHIS CENTER 133.65 292.15	CTAF 122.9
-------------------	---------------------------------	---------------



2400 ↑		UMEMY ✦		ZOXUM 4 NM Holding Pattern		
RW33 2 NM		ZESBO 2 NM to RW33 WEPKI 332° 1900 3.00° TCH 40		7 NM		
CATEGORY		A		B	C	D
LNAV MDA		740-1		471 (500-1)	740-1 $\frac{3}{8}$ 471 (500-1 $\frac{3}{8}$)	NA
CIRCLING		860-1		591 (600-1)	900-1 $\frac{3}{4}$ 631 (700-1 $\frac{3}{4}$)	NA