

WAAS

CH **69318**

W30A

APP CRS

296°

Rwy Idg

5650

TDZE

2131

Apt Elev

2135

RNAV (GPS) RWY 30

WATFORD CITY MUNI (S25)

RNP APCH - GPS.

VDP NA when using Williston altimeter setting. When local altimeter setting not received, use Williston Basin Int altimeter setting: increase LPV DA to 2488 feet; all visibility ¼ SM. Increase all MDAs 120 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C/D ½ SM.

MISSED APPROACH: Climb to 4500 direct GERHE and hold.

AWOS-3PT 118.125	SALT LAKE CENTER 126.85 305.2	UNICOM 122.8 (CTAF) 0
----------------------------	---	---------------------------------

Procedure NA for arrivals at POVNY on V71 northwest bound.

(IAF) POVNY

4300 NoPT 20° (11)

2306

2428

2862

2684

2851

(FAF) BOWIS

4100 296° (4.1)

(IF/IAF) CIPGO

116° 5 NM

HOLD 6000 4300

MISSED APCH FIX

5 NM 16° 296°

GERHE

4300 NoPT 026° (14)

(IAF) HASOS

3492

Procedure NA for arrivals at HASOS on V439 southeast bound.

ELEV 2135	D	TDZE 2131		
4500	GERHE	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 45).		
5 NM	Holding Pattern			
1.6 NM to RWY30	BOWIS	4100		
4.5 NM	CIPGO	116° 6000 296° 4300		
4.1 NM		GP 3.00° TCH 40		
CATEGORY	A	B	C	D
LPV DA	2381-3¼ 250 (300-¾)			
LNAV MDA	2680-1	549 (600-1)	2680-1½	549 (600-1½)
C CIRCLING	2700-1 565 (600-1)	2760-1 625 (700-1)	2760-1¾ 625 (700-1¾)	2960-2¾ 825 (900-2¾)

WATFORD CITY, NORTH DAKOTA

Amdt 1A 03NOV22

47°48'N-103°15'W

WATFORD CITY MUNI (S25)

RNAV (GPS) RWY 30