



WAAS CH 82442 W35A	APP CRS 352°	Rwy Idg TDZE Apt Elev	4600 3187 3187
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 35

FLOYDADA MUNI (41F')

RNP APCH. ▼ ▲ NA Rwy 35 helicopter visibility reduction below ¾ SM NA. Use Plainview altimeter setting, when not received, use Lubbock altimeter setting and increase all MDA 20 feet; increase LP Cat C visibility ½ SM and Circling Cat C visibility ¼ mile.		MISSED APPROACH: Climbing left turn to 5000 direct ASACI and hold.
---	--	--

PVW AWOS-3 119.675	LUBBOCK APP CON 119.2 351.8	UNICOM 122.8 (CTAF) 0
------------------------------	---------------------------------------	---------------------------------



5000 ASACI		Visual Segment - Obstacles.		5 NM Holding Pattern	
RW35		CINAV	ASACI	172° → 6000	← 352° 5000
5 NM		6 NM			
CATEGORY	A	B	C	D	
LP MDA	3760-1	573 (600-1)	3760-1½ 573 (600-1½)	NA	
LNAV MDA	3840-1	653 (700-1)	3840-1⅞ 653 (700-1⅞)	NA	
◼ CIRCLING	3840-1 653 (700-1)	3920-1 733 (800-1)	3980-2¼ 793 (800-2¼)	NA	