

RADAR INSTRUMENT APPROACH MINIMUMS

HUNTINGTON, WV

Amdt 8A, 23JUN16 (21112) (FAA)

ELEV 828

TRI-STATE/MILTON J FERGUSON FLD (HTS)

RADAR-1 119.75 270.1 

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/ MDA-VIS</u>	<u>HAT/ HAA</u>	<u>CEIL-VIS</u>
ASR	12		ABCD	1280/40	452	(500-¾)				
	30		AB	1300-1	472	(500-1)	CD	1300-1⅓	472	(500-1⅓)
CIR			AB	1340-1	512	(600-1)	C	1340-1½	512	(600-1½)
			D	1420-2	592	(600-2)				

Inoperative table does not apply to ASR S-12 CATs A and B.
For inoperative MALSR increase ASR S-12 CATs C and D visibility to RVR 5000.
Rwy 12 helicopter visibility reduction below ¾ SM not authorized.

16 MAY 2024 to 13 JUN 2024

16 MAY 2024 to 13 JUN 2024