

RADAR INSTRUMENT APPROACH MINIMUMS

CAMPBELL AAF (KHOP), Fort Campbell, KY RADAR 1 Amdt 2
RADAR 2 Amdt 3 02NOV23 (23306) (USA)
RADAR - (E) 134.350x 237.5x 395.9x 258.3x 290.9x 

ELEV 571

	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
RADAR-1						
ASR ¹	5 ^{2 3 4 5}		AB	980-1	425	(500-1)
			CDE	980-1¼	425	(500-1¼)
	23 ^{2 6 7 8 9}		AB	980/24	409	(500-½)
			CDE	980/40	409	(500-¾)
CIR ¹⁰	5-23		AB	1060-1	489	(500-1)
			C	1060-1½	489	(500-1½)
			DE	1140-2	569	(600-2)
RADAR-2						
PAR ^{11 12}	23 ^{2 6 13 14 15}	3.0°/55/1143	ABCDE	771/24	200	(200-½)
	5 ^{2 3 14 16}	3.0°/50/941	ABCDE	755-¾	200	(200-¾)

¹VGSI and descent angles not coincident.
²Procedure NA when R-3701, R-3702A/B in use.
³Final approach course 045°.
⁴Recommended altitude 4 miles: 1880, 3 miles: 1560, 2 miles: 1240.
⁵FAF 5.0 miles from thld, min alt 2200.
⁶Final approach course 225°.
⁷Recommended altitude 4 miles: 1900, 3 miles: 1580, 2 miles: 1260.
⁸FAF 4.9 NM from thld, min alt 2200.
⁹When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE RVR to 60, vis to 1½ miles.
¹⁰Circling NA SE of Rwy 5-23.
¹¹PAR unavbl daily 0400-1400Z+.
¹²VGSI and PAR glidepath not coincident.
¹³FAF 4.9 NM from thld.
¹⁴Glideslope intercept altitude 2200.
¹⁵When ALS inop, increase RVR to 40, vis to ¾ mile.
¹⁶FAF 5.0 NM from thld.

KNOXVILLE, TN Amdt 23, 12AUG21 (21224) (FAA) ELEV 986
MC GHEE TYSON (TYS)
RADAR-1 123.9 360.8  

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR	5L		AB	1420/24	467	(500-½)	CDE	1420/50	467	(500-1)
	5R		AB	1420-1	461	(500-1)	CDE	1420-1%	461	(500-1%)
	23R		AB	1500/24	516	(600-½)	CDE	1500/55	516	(600-1)
	23L		AB	1500-55	534	(600-1)	CDE	1500-1½	534	(600-1½)
 CIRCLING ALL RWY			A	1500-1	514	(600-1)	B	1560-1	574	(600-1)
			C	1660-2	674	(700-2)	DE	1900-3	914	(1000-3)

For inoperative ALS increase ASR-5L and ASR-23R CAT C/D/E visibility to 1% SM.

18 APR 2024 to 16 MAY 2024

18 APR 2024 to 16 MAY 2024

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

SABRE AAF (KEOD), TN (Fort Campbell), (Amdt 3A, 18032 USA)
RADAR - (E) 118.1 340.9  NA

ELEV 595

ASR	<u>RWY</u>	<u>GS/TCH/RPI</u>	<u>CAT</u>	<u>DH/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
	23		COPTER	1060-½	473	(500-½)
	5		COPTER	1100-½	507	(600-½)

18 APR 2024 to 16 MAY 2024

18 APR 2024 to 16 MAY 2024

RADAR INSTRUMENT APPROACH MINIMUMS